



**Profil-Flanschdichtung metrisch
Für Vorschweissbunde ohne Fase**

Ausführung:

- Passend zu Vorschweissbund Nr. 27 79 85 PP-H SDR11 ohne Fase
- Profil-Flanschdichtung mit Stahleinlage (Typ G-ST-P/K)
- Härte: 70° Shore **EPDM**, 75° Shore **FPM**

d (mm)	DN (mm)	PN (bar)	EPDM Code	SP	Gewicht (kg)	FPM Code	SP	Gewicht (kg)
20	15	16	748 440 706	0	0.009	749 440 706	0	0.013
25	20	16	748 440 707	0	0.015	749 440 707	0	0.014
32	25	16	748 440 708	0	0.013	749 440 708	0	0.019
40	32	16	748 440 709	0	0.019	749 440 709	0	0.026
50	40	16	748 440 710	0	0.029	749 440 710	0	0.039
63	50	16	748 440 711	0	0.041	749 440 711	0	0.050
75	65	16	748 440 712	0	0.053	749 440 712	0	0.082
90	80	16	748 440 713	0	0.064	749 440 713	0	0.083

d (mm)	DN (mm)	PN (bar)	D (mm)	D1 (mm)	di VSB/BB (mm)	H (mm)	H1 (mm)
20	15	16	51	20	10 - 20	4	3
25	20	16	61	22	12 - 22	4	3
32	25	16	71	28	18 - 28	4	3
40	32	16	82	40	30 - 40	4	3
50	40	16	92	46	36 - 46	4	3
63	50	16	107	58	48 - 58	5	4
75	65	16	127	69	59 - 69	5	4
90	80	16	142	84	73 - 84	5	4