



JRGUMAT Thermomischer, PN 10 3400



Gehäuse aus Rotguss, allseitig Aussengewinde für Verschraubungen, max. Warmwasser Temp.: 90 °C. Standard-Temperaturen 25/40/48/55 °C. Jeweils mit Sechskantstiftschlüssel verstellbar. Kappe für Zirkulationsanschluss zu 3400 siehe 8325.

Lief.-Nr.	GN	DN	d2	°C		Art.-Nr.	
				manuell			
3400.910	1/2"	15	G 1 1/8"	20-30	5	25	32201-0362
3400.912	1/2"	15	G 1 1/8"	30-45	5	40	32201-0363
3400.914	1/2"	15	G 1 1/8"	35-55	5	48	32201-0364
3400.916	1/2"	15	G 1 1/8"	45-65	5	55	32201-0365
3400.920	3/4"	20	G 1 1/4"	20-30	5	25	32201-0366
3400.922	3/4"	20	G 1 1/4"	30-45	5	40	32201-0367
3400.924	3/4"	20	G 1 1/4"	35-55	5	48	32201-0368
3400.926	3/4"	20	G 1 1/4"	45-65	5	55	32201-0369
3400.930	1"	25	G 1 1/2"	20-30	5	25	32201-0370
3400.932	1"	25	G 1 1/2"	30-45	5	40	32201-0371
3400.934	1"	25	G 1 1/2"	35-55	5	48	32201-0372
3400.936	1"	25	G 1 1/2"	45-65	5	55	32201-0373
3400.940	1 1/4"	32	G 2"	20-30	8	25	32201-0374
3400.942	1 1/4"	32	G 2"	30-45	8	40	32201-0375
3400.944	1 1/4"	32	G 2"	35-55	8	48	32201-0376
3400.946	1 1/4"	32	G 2"	45-65	8	55	32201-0377
3400.950	1 1/2"	40	G 2 1/4"	20-30	8	25	32201-0378
3400.952	1 1/2"	40	G 2 1/4"	30-45	8	40	32201-0379
3400.954	1 1/2"	40	G 2 1/4"	35-55	8	48	32201-0380
3400.956	1 1/2"	40	G 2 1/4"	45-65	8	55	32201-0381
3400.960	2"	50	G 2 3/4"	20-30	8	25	32201-0382
3400.962	2"	50	G 2 3/4"	30-45	8	40	32201-0383
3400.964	2"	50	G 2 3/4"	35-55	8	48	32201-0384
3400.966	2"	50	G 2 3/4"	45-65	8	55	32201-0385

2400