



Flanschen–Kaliberwechsel Fig. 2084 (FFR)



aus duktilem Gusseisen, Epoxy–Beschichtung.

Lief.–Nr.	DN1 mm	DN2 mm	PN bar	L mm	NPK	Art.–Nr.
150213	80	40	10 / 16	200	244.138	33101–0092
150214	80	50	10 / 16	200	244.158	33101–0093
150216	100	40	10 / 16	200	244.139	33101–0095
150217	100	50	10 / 16	200	244.159	33101–0096
150218	100	65	10 / 16	200	244.179	33101–0097
150219	100	80	10 / 16	200	244.219	33101–0098
150220	125	65	10 / 16	305	244.181	33101–0099
150221	125	80	10 / 16	200	244.221	33101–0100
150222	125	100	10 / 16	200	244.241	33101–0101
150223	150	80	10 / 16	200	244.222	33101–0102
150224	150	100	10 / 16	200	244.242	33101–0103
150225	150	125	10 / 16	200	244.262	33101–0104
150228	200	100	10	300	244.243	33101–0105
150230	200	125	10	300	244.263	33101–0106
150232	200	150	10	300	244.283	33101–0107
150238	250	125	10	300	244.264	33101–0108
150240	250	150	10	300	244.284	33101–0109
150242	250	200	10	300	244.324	33101–0110
150244	300	150	10	300	244.285	33101–0111
150246	300	200	10	300	244.325	33101–0112
150248	300	250	10	300	244.346	33101–0113

2500