

WIL



Wild Steckmuffen Rohre Novo-Sit HOZ-ZMU

- Aus duktilem Gusseisen
- Innen Hochofen-Zementmörtel (HOZ)
- Aussen Zementmörtelumhüllung (ZMU)
- Doppelkammer-Steckmuffensystem UNIVERSAL Novo-Sit
- Inklusive Dichtring TYTON
- Elektrisch nicht leitende Verbindung



Orig. Nr.	DN	Klasse	D	s1	s2	s3	Länge	kg/m	Gewicht	NPK-Nr.	Ⓜ	CHF
			mm	mm	mm	mm	mm		kg		m	m
HOZ ZMU100C100N	100	C100	118	4.7	4	5	5970	22.3	22	213.412	6 33110-0613	96.00
HOZ ZMU125C64N	125	C64	144	4.0	4	5	5970	27.7	27	213.413	6 33110-0614	121.00
HOZ ZMU150C64N	150	C64	170	4.0	4	5	5970	32.6	32	213.414	6 33110-0615	145.00
HOZ ZMU200C64N	200	C64	222	5.0	4	5	5970	44.7	44	213.415	6 33110-0616	202.00
HOZ ZMU250C50N	250	C50	274	4.8	4	5	5970	58.9	58	213.416	6 33110-0617	292.00

Klasse: Zulässiger PFA in bar

