

Wild Spitzend-T-Stück Typ IT

- Mit 3 Stutzen, aus duktilem Gusseisen
- Innen emailliert, aussen bituminiert
- Für Trink- und Rohwasser



Orig. Nr.	DN1 mm	DN2 mm	L mm	l mm	e1 mm	e2 mm	Gewicht kg	NPK-Nr.	Stück	CHF Stück	
IT100-80	100	80	550	275	7.2	7.0	14.0	234.472	1	33110-0236	380.00
IT100-100	100	100	550	275	7.2	7.2	15.0	234.412	1	33110-0237	380.00
IT125-80	125	80	600	300	7.5	7.0	16.0	234.473	1	33110-0240	590.00
IT125-100	125	100	600	300	7.5	7.2	17.0	234.513	1	33110-0241	590.00
IT125-125	125	125	600	300	7.5	7.5	19.0	234.413	1	33110-0242	590.00
IT150-80	150	80	620	310	7.8	7.0	15.0	234.474	1	33110-0245	628.00
IT150-100	150	100	620	310	7.8	7.2	16.0	234.514	1	33110-0246	628.00
IT150-125	150	125	620	310	7.8	7.5	18.0	234.534	1	33110-0247	628.00
IT150-150	150	150	620	310	7.8	7.8	20.0	234.414	1	33110-0248	628.00
IT200-80	200	80	650	325	8.4	7.0	22.0	234.475	1	33110-0249	876.00
IT200-100	200	100	650	325	8.4	7.2	25.0	234.515	1	33110-0250	876.00
IT200-125	200	125	650	325	8.4	7.8	27.0	234.535	1	33110-0251	876.00
IT200-150	200	150	650	325	8.4	8.4	30.0	234.555	1	33110-0252	876.00
IT200-200	200	200	650	325	8.4	9.0	35.0	234.415	1	33110-0253	876.00
IT250-100	250	100	870	435	9.0	7.2	47.0	234.516	1	33110-0888	2'121.00
IT250-150	250	150	870	435	9.0	7.8	48.5	234.556	1	33110-0889	2'121.00
IT250-200	250	200	870	435	9.0	8.4	51.5	234.576	1	33110-0890	2'121.00
IT250-250	250	250	870	435	9.0	9.0	55.0	234.416	1	33110-0891	2'121.00

Auf Anfrage: Vollschutz etec-Email, Vollschutz Epoxy-Pulverbeschichtung

