

**STM-Reduktion, 2-muffig Novo-Sit Typ MMR**

Aus duktilem Gusseisen, innen emailliert, aussen bituminiert, Doppelkammer-Steckmuffen-system Novo-Sit, inklusive Dichtring TYTON.

Für Trink- und Rohwasser.

Lief.-Nr.	DN1 mm	DN2 mm	Lu mm	t 1 mm	t 2 mm	NPK	Art.-Nr.
MMR100-80N	100	80	90	129	119	236.519	33110-0254
MMR125-80N	125	80	140	126	119	236.521	33110-0255
MMR125-100N	125	100	100	126	123	236.541	33110-0256
MMR150-80N	150	80	190	129	119	236.522	33110-0257
MMR150-100N	150	100	150	129	123	236.542	33110-0258
MMR150-125N	150	125	100	129	126	236.562	33110-0259
MMR200-100N	200	100	250	138	123	236.543	33110-0260
MMR200-125N	200	125	200	138	126	236.563	33110-0261
MMR200-150N	200	150	150	138	129	236.583	33110-0262
MMR250-125N	250	125	300	143	123	236.564	33110-0263
MMR250-150N	250	150	250	143	129	236.584	33110-0264
MMR250-200N	250	200	150	143	138	236.624	33110-0265
MMR300-150N	300	150	350	152	129	236.585	33110-0266
MMR300-200N	300	200	250	152	138	236.625	33110-0267
MMR300-250N	300	250	150	152	143	236.645	33110-0268

2571

Auf Anfrage: Vollschutz etec-Email. Vollschutz Epoxy-Pulverbeschichtung.