

**SM-Tee, 1-muffig mit Flanschabzweig Typ A**

Aus duktilem Gusseisen, innen emailliert, aussen bituminiert, Schraubmuffensystem inklusiver elektrische Überbrückung.

Für Trink- und Rohwasser.

Lief.-Nr.	DN1 mm	DN2 mm	PN bar	Lu mm	l mm	t mm	NPK	Art.-Nr.
A100-80U	100	80	10 / 16	400	200	88	223.219	33110-0501
A100-100U	100	100	10 / 16	400	200	88	223.119	33110-0502
A125-80U	125	80	10 / 16	425	190	91	223.221	33110-0505
A125-100U	125	100	10 / 16	425	195	91	223.241	33110-0506
A125-125U	125	125	10 / 16	425	200	91	223.121	33110-0507
A150-80U	150	80	10 / 16	450	205	94	223.222	33110-0510
A150-100U	150	100	10 / 16	450	210	94	223.242	33110-0511
A150-125U	150	125	10 / 16	450	210	94	223.262	33110-0512
A150-150U	150	150	10 / 16	450	210	94	223.122	33110-0513
A200-100U	200	100	10 / 16	600	250	100	223.243	33110-0516
A200-150U	200	150	10 / 16	600	275	100	223.283	33110-0517
A200-200U10	200	200	10	600	300	100	223.123	33110-0518

2571

Auf Anfrage: Vollschutz etec-Email. Vollschutz Epoxy-Pulverbeschichtung.