

**SM-Reduktion, 2-Muffig Typ MMR**

Aus duktilem Gusseisen, innen emailliert, aussen bituminiert, Schraubmuffensystem inklusiver elektrische Überbrückung.

Für Trink- und Rohwasser.

Lief.-Nr.	DN1 mm	DN2 mm	Lu mm	t 1 mm	t 2 mm	NPK	Art.-Nr.
MMR100-80U	100	80	90	88	84	226.519	33110-0532
MMR125-80U	125	80	140	91	84	226.521	33110-0533
MMR125-100U	125	100	100	91	88	226.541	33110-0534
MMR150-80U	150	80	190	94	84	226.522	33110-0535
MMR150-100U	150	100	150	94	88	226.542	33110-0536
MMR150-125U	150	125	100	94	91	226.562	33110-0537
MMR200-100U	200	100	250	100	88	226.543	33110-0538
MMR200-125U	200	125	200	100	91	226.563	33110-0539
MMR200-150U	200	150	150	100	94	226.583	33110-0540
MMR250-125U	250	125	300	106	91	226.564	33110-0541
MMR250-150U	250	150	250	106	94	226.584	33110-0542
MMR250-200U	250	200	150	106	100	226.624	33110-0543

2571

Auf Anfrage: Vollschutz etec-Email. Vollschutz Epoxy-Pulverbeschichtung.