

**SM-Flansch-Muffenstück schlaufbar Typ EU**

Aus duktilem Gusseisen, innen emailliert, aussen bituminiert, Schraubmuffensystem inklusiver elektrische Überbrückung.

Für Trink- und Rohwasser.

Lief.-Nr.	DN mm	PN bar	Lu mm	z mm	t mm	NPK	Art.-Nr.
EU40U	40	10 / 16	76	50+/-30	74	225.815	33110-0556
EU50U	50	10 / 16	78	50+/-30	77	225.816	33110-0557
EU80U	80	10 / 16	130	86+/-40	84	225.818	33110-0558
EU100U	100	10 / 16	130	87+/-40	88	225.819	33110-0559
EU125U	125	10 / 16	135	91+/-40	91	225.841	33110-0560
EU150U	150	10 / 16	135	92+/-40	94	225.842	33110-0561
EU200U10	200	10	140	97+/-40	100	225.823	33110-0562
EU200U16	200	16	140	97+/-40	100	225.843	33110-0565
EU250U10	250	10	145	102+/-40	106	225.824	33110-0563
EU250U16	250	16	145	102+/-40	106	225.844	33110-0566
EU300U10	300	10	150	107+/-40	110	225.825	33110-0564
EU300U16	300	16	150	107+/-40	110	225.845	33110-0567

2571

Auf Anfrage: Vollschutz etec-Email. Vollschutz Epoxy-Pulverbeschichtung.