



## Wild Flanschverbindungen rostfrei INOX A2

• Bestehend aus der Flanschdichtung G-ST / Guss, Schrauben, Muttern und zwei Unterlagsscheiben

Orig. Nr.	DN bar	PN	D mm	b mm	k mm	h mm	d2 mm	d4 mm	f mm	Grösse MxL mm mm	Schrauben Stück	Gewicht kg	NPK-Nr.	CHF Stück	
FLV40A2	40	10/16	150	19.0	110	39	19	84	3	M16x60	4	0.6	274.217	1 33110-0972	29.00
FLV50A2	50	10/16	165	19.0	125	40	19	93	3	M16x60	4	0.6	274.218	1 33110-0973	29.00
FLV80A2	80	10/16	200	19.0	160	43	19	132	3	M16x65	8	1.2	274.221	1 33110-0974	45.00
FLV100A2	100	10/16	220	19.0	180	45	19	156	3	M16x65	8	1.2	274.222	1 33110-0975	48.00
FLV125A2	125	10/16	250	19.0	210	48	19	184	3	M16x70	8	1.2	274.223	1 33110-0976	49.00
FLV150A2	150	10/16	285	19.0	240	50	23	211	3	M20x75	8	2.5	274.224	1 33110-0977	87.00
FLV200A210	200	10	340	20.0	295	55	23	266	3	M20x80	8	2.5	274.245	1 33110-0978	93.00
FLV200A216	200	16	340	20.0	295	55	23	266	3	M20x80	12	3.8	274.265	1 33110-0979	125.00
FLV250A210	250	10	400	22.0	350	60	23	319	3	M20x80	12	3.8	274.246	1 33110-0980	132.00
FLV250A216	250	16	400	22.0	350	60	28	319	3	M24x90	12	5.9	274.266	1 33110-0981	250.00
FLV300A210	300	10	455	24.5	400	65	23	370	4	M20x80	12	3.8	274.247	1 33110-0982	163.00
FLV300A216	300	16	455	24.5	410	65	28	370	4	M24x90	12	6.9	274.267	1 33110-0983	278.00

