

Hawle Spitzend/Steckmuffen-Reduktion Baio 5360, PN 16

- BAIO Baukasten-System, Gehäuse: Sphäroguss EN-GJS-400 (GGG 40)
- EWS-beschichtet nach RAL GSK bis 40°C, Schichtdicke min. 250 µm
- Steckmuffen nach DIN 28603, Dichtungen EPDM, mit KTW-Zertifizierung



Orig.-Nr.	DN1 mm	DN2 mm	PN bar	L mm	s mm	t mm	Gewicht kg	NPK-Nr.	☐ Stück	CHF Stück	
5360100080	100	80	16	310	95	105	7.0	236.219	1	33211-0183	224.00
5360125080	125	80	16	370	100	105	9.4	236.221	1	33211-0184	296.00
5360125100	125	100	16	340	100	120	9.0	236.241	1	33211-0185	300.00
5360150080	150	80	16	420	100	105	10.8	236.222	1	33211-0186	336.00
5360150100	150	100	16	395	100	120	11.8	236.242	1	33211-0187	352.00
5360150125	150	125	16	335	100	125	12.4	236.262	1	33211-0188	367.00
5360200100	200	100	16	500	105	120	17.4	236.243	1	33211-0189	460.00
5360200125	200	125	16	435	105	125	18.2	236.263	1	33211-0190	467.00
5360200150	200	150	16	410	105	125	17.2	236.283	1	33211-0191	476.00
5360250150	250	150	16	430	105	125	30.0		1	33211-2770	611.00
5360250200	250	200	16	475	150	145	30.3		1	33211-2772	618.00
5360300100	300	100	16	450	105	120	42.0		1	33211-2774	803.00
5360300150	300	150	16	480	105	125	47.0		1	33211-2776	838.00
5360300200	300	200	16	625	165	145	50.2		1	33211-2778	856.00
5360300250	300	250	16	525	165	145	53.0		1	33211-2780	887.00

