

**Hawle Spitzend/Steckm.-Reduktion BLS 5330**

- Mit Schweissraupe, Gehäuse: Sphäroguss EN-GJS-400 (GGG 40)
- EWS-beschichtet nach RAL GSK bis 40°C, Schichtdicke min. 250 µm
- Steckmuffen nach DIN 28603, Dichtungen EPDM, mit KTW-Zertifizierung



| Orig.-Nr.  | DN1<br>mm | DN2<br>mm | PN<br>bar | L<br>mm | t<br>mm | Gewicht<br>kg | NPK-Nr. | Stück | CHF<br>Stück |        |
|------------|-----------|-----------|-----------|---------|---------|---------------|---------|-------|--------------|--------|
| 5330125100 | 125       | 100       | 16        | 330     | 135     | 11.25         | 236.241 | 1     | 33211-0817   | 327.00 |
| 5330150100 | 150       | 100       | 16        | 340     | 135     | 13.68         | 236.242 | 1     | 33211-0624   | 354.00 |
| 5330150125 | 150       | 125       | 16        | 360     | 143     | 16.30         | 236.262 | 1     | 33211-0625   | 379.00 |
| 5330200100 | 200       | 100       | 16        | 365     | 135     | 16.40         | 236.243 | 1     | 33211-0818   | 455.00 |
| 5330200125 | 200       | 125       | 16        | 360     | 143     | 18.00         | 236.263 | 1     | 33211-0626   | 466.00 |
| 5330200150 | 200       | 150       | 16        | 365     | 150     | 18.00         | 236.283 | 1     | 33211-0627   | 493.00 |
| 5330250200 | 250       | 200       | 16        | 385     | 160     | 33.00         | 236.324 | 1     | 33211-0845   | 685.00 |
| 5330300200 | 300       | 200       | 16        | 415     | 160     | 41.00         | 236.325 | 1     | 33211-0846   | 932.00 |
| 5330300250 | 300       | 250       | 16        | 400     | 165     | 47.00         | 236.345 | 1     | 33211-0847   | 975.00 |

