



## Flanschen-T-Stück, PN 10/16, 8510



Achtung: Sonderlängen bis 2000 mm sowie Sonderformen nach Skizze in St 37, mit EWS-Beschichtung, auf Anfrage.

Gehäuse: Sphäroguss EN-GJS-400 (GGG 40), EWS-Beschichtung nach GSK.

Betriebstemperatur max. 40 °C

Lief.-Nr.	DN1 mm	DN2 mm	PN bar	L mm	h mm	NPK	Art.-Nr.
8510050050	50	50	16	300	150	247.116	33211-1523
8510065050	65	50	16	330	155	247.157	33211-1524
8510065065	65	65	16	330	165	247.117	33211-1525
8510080050	80	50	16	330	160	247.158	33211-1526
8510080065	80	65	16	330	165	247.178	33211-1527
8510080080	80	80	16	330	165	247.118	33211-1528
8510100050	100	50	16	360	170	247.159	33211-1529
8510100065	100	65	16	360	170	247.179	33211-1530
8510100080	100	80	16	360	175	247.219	33211-1531
8510100100	100	100	16	360	180	247.119	33211-1532
8510125050	125	50	16	400	185	247.161	33211-1533
8510125065	125	65	16	400	185	247.181	33211-1534
8510125080	125	80	16	400	190	247.221	33211-1535
8510125100	125	100	16	400	195	247.241	33211-1536
8510125125	125	125	16	400	200	247.121	33211-1537
8510150050	150	50	16	440	200	247.162	33211-1538
8510150065	150	65	16	440	200	247.182	33211-1539
8510150080	150	80	16	440	205	247.222	33211-1540
8510150100	150	100	16	440	210	247.242	33211-1541
8510150125	150	125	16	440	215	247.262	33211-1542
8510150150	150	150	16	440	220	247.122	33211-1543
8510200080	200	80	10	520	235	243.223	33211-1545
8510201080	200	80	16	520	235	247.223	33211-1551
8510200100	200	100	10	520	240	243.243	33211-1546
8510201100	200	100	16	520	240	247.243	33211-1552
8510200125	200	125	10	520	245	243.263	33211-1547
8510201125	200	125	16	520	245	247.263	33211-1553
8510200150	200	150	10	520	250	243.283	33211-1548
8510201150	200	150	16	520	250	247.283	33211-1554
8510200200	200	200	10	520	260	243.123	33211-1549
8510201201	200	200	16	520	260	247.123	33211-1555

2596