

**Hawle Flanschdichtung mit Stahleinlage 8200**

- Mit Stahleinlage zur Erleichterung der Montage und für dauerhaft sicheren Sitz
- Werkstoff: EPDM, Andere Nennweiten und Druckstufen auf Anfrage



Orig. Nr.	DN	Ø d mm	Ø D mm	PN bar	s mm	Gewicht kg	NPK-Nr.	Stück	CHF Stück	
8200040000	40	49	92	10-40	4	0.03	877.615	1	33211-0340	9.00
8200050000	50	61	107	10-40	4	0.04	877.616	1	33211-0341	10.00
8200065000	65	77	127	10-40	4	0.06	877.617	1	33211-0342	10.00
8200080000	80	89	142	10-40	4	0.07	877.618	1	33211-0343	10.00
8200100000	100	115	162	10-16	5	0.08	877.619	1	33211-0344	12.00
8200125000	125	141	192	10-16	5	0.10	877.621	1	33211-0345	13.00
8200150000	150	169	218	10-16	6	0.12	877.622	1	33211-0346	16.00
8200200000	200	220	273	10-16	6	0.24	877.623	1	33211-0347	20.00
8200250000	250	273	328	10	6	0.27	877.624	1	33211-1947	21.00
8200250016	250	273	229	16	6	0.28	877.624	1	33211-0348	22.00
8200300000	300	324	378	10	6	0.30	877.625	1	33211-1948	31.00
8200300016	300	324	384	16	6	0.36	877.625	1	33211-0349	33.00
8200350000	350	356	438	10	7	0.30	877.626	1	33211-2161	39.00
8200350016	350	368	445	16	7	0.36	877.626	1	33211-2159	40.00
8200400000	400	420	490	10	7	0.47	877.627	1	33211-1950	44.00
8200400016	400	420	497	16	7	0.47	877.627	1	33211-1949	45.00

