

**Hawle Spitzend-Steckmuffen-Schieber 4510, PN 16**

- BAIO Baukasten-System, Gehäuse: Sphäroguss EN-GJS-400 (GGG 40)
- EWS-beschichtet nach RAL GSK bis 40°C, Schichtdicke min. 250 µm
- Steckmuffen nach DIN 28603, Dichtungen EPDM, mit KTW-Zertifizierung



Orig.-Nr.	DN	Ø d	PN	H	L	L1	t	s	Gewicht	NPK-Nr.	Stück	CHF	
	mm	mm	bar	mm	mm	mm	mm	mm	kg			Stück	
4510080000	80	98	16	335	295	145	110	75	14.6	812.218	1	33211-0075	604.00
4510100000	100	118	16	375	320	170	105	95	17.2	812.219	1	33211-0076	669.00
4510125000	125	144	16	450	350	175	115	100	24.8	812.221	1	33211-0077	922.00
4510150000	150	170	16	460	360	190	115	100	31.6	812.222	1	33211-0078	1'085.00
4510200000	200	222	16	565	390	210	125	105	61.0	812.223	1	33211-0079	1'793.00
4510250000	250	274	16	649	535	295	175	150	105.4		1	33211-2708	1'793.00
4510300000	300	326	16	731	600	330	200	165	154.8		1	33211-2710	1'793.00

