

**Hawle Combi-T mit Steckmuffen 4370, PN 16**

- BAIO Baukasten-System, Gehäuse: Sphäroguss EN-GJS-400 (GGG 40)
- EWS-beschichtet nach RAL GSK bis 40°C, Schichtdicke min. 250 µm
- Steckmuffen nach DIN 28603, Dichtungen EPDM, mit KTW-Zertifizierung



Orig.-Nr.	DN1 mm	DN2 mm	PN bar	L mm	H mm	h mm	h1 mm	t1 mm	t2 mm	Gewicht kg	NPK-Nr.	Stück	CHF Stück
4370080080	80	80	16	410	335	220	78	105	105	24.0	823.311	1 33211-0100	797.00
4370100080	100	80	16	435	335	230	88	120	105	26.0	823.352	1 33211-0101	851.00
4370100100	100	100	16	455	375	255	90	120	120	31.0	823.312	1 33211-0102	1'007.00
4370125080	125	80	16	430	335	240	105	125	105	27.5	823.353	1 33211-0103	1'005.00
4370125100	125	100	16	435	375	270	105	125	120	34.0	823.363	1 33211-0104	1'127.00
4370125125	125	125	16	440	450	290	115	125	125	40.0	823.313	1 33211-0105	1'376.00
4370150080	150	80	16	450	335	260	116	125	105	33.0	823.354	1 33211-0106	1'011.00
4370150100	150	100	16	475	375	280	115	125	120	40.0	823.364	1 33211-0107	1'163.00
4370150125	150	125	16	565	450	295	120	125	125	43.5	823.374	1 33211-0108	1'488.00
4370150150	150	150	16	565	460	300	120	125	125	52.0	823.314	1 33211-0109	1'626.00
4370200080	200	80	16	490	335	280	138	145	105	41.0	823.355	1 33211-0110	1'233.00
4370200100	200	100	16	515	375	305	140	145	120	50.0	823.365	1 33211-0111	1'420.00
4370200125	200	125	16	605	450	320	147	145	125	53.0	823.375	1 33211-0112	1'635.00
4370200150	200	150	16	605	460	325	147	145	125	65.5	823.385	1 33211-0113	1'881.00
4370200200	200	200	16	670	565	355	150	145	145	88.3	823.315	1 33211-0114	2'558.00

