



Combi-III mit Steckmuffen 4490, PN 16



Achtung: x = Kombination aus Basis Formstück (Nr. 5420) und Schieber (Nr. 4510).
 Gehäuse: EN-GJS-400 (GGG 40), Steckmuffen nach DIN 28603, EWS-Beschichtung nach GSK, Dichtungen EPDM mit KTW-Zulassung.

Betriebstemperatur max. 40 °C

Lief.-Nr.	DN1 mm	DN2 mm	L mm	L1 mm	h mm	h1 mm	NPK	Art.-Nr.
4490080080	80	80	830	530	220	78	825.311	33211-0695
4490100080	100	80	865	565	230	88	825.352	33211-0696
4490100100	100	100	885	585	255	90	825.312	33211-0146
4490125080	125	80	910	560	240	105	825.353	33211-0697
4490125100	125	100	915	565	270	105	825.363	33211-0150
4490125125	125	125	920	570	290	115	825.313	33211-0147
4490150080	150	80	950	610	260	116	825.354	33211-0698
4490150100	150	100	975	635	280	115	825.364	33211-0151
4490150125	150	125	1065	725	295	120	825.374	33211-0153
4490150150	150	150	1065	725	300	120	825.314	33211-0148
4490200080	200	80	1040	680	280	138	825.355	33211-0699
4490200100	200	100	1065	705	305	140	825.365	33211-0152
4490200125	200	125	1155	795	320	147	825.375	33211-0154
4490200150	200	150	1155	795	325	147	825.385	33211-0155
4490200200	200	200	1220	860	355	150	825.315	33211-0149
4490250080 x	250	80	1290	810	485	355	825.356	33211-0700
4490250100 x	250	100	1310	830	520	370	825.366	33211-0701
4490250150 x	250	150	1390	910	565	395	825.386	33211-0703
4490250200 x	250	200	1445	965	615	435	825.416	33211-0704
4490250250 x	250	250	1485	1005	750	510	825.316	33211-0705
4490300080 x	300	80	1455	915	515	365	825.357	33211-0706
4490300100 x	300	100	1455	915	545	395	825.367	33211-0707
4490300150 x	300	150	1520	980	590	420	825.387	33211-0709
4490300200 x	300	200	1580	1040	655	475	825.417	33211-0710
4490300300 x	300	300	1680	1140	845	575	825.317	33211-0711