

**Hawle PE-Steckmuffen-Schieber 4040, PN 16**

- PE- und PVC-Rohre können direkt und schubsicher montiert werden
- Flansch und Spannring EN-GJS-400 (GGG 40), EWS-beschichtet nach RAL GSK bis 40°C
- Dichtungen EPDM, mit KTW-Zertifizierung, Schrauben A2 1.4306



Orig.-Nr.	DN	Ø d mm	PN bar	H mm	L mm	t mm	Gewicht kg	NPK-Nr.	Stück	CHF Stück	
4040050063	50	63	16	260	225	85	10.5	814.515	1	33211-1189	460.00
4040065075	65	75	16	330	240	85	15.5	814.516	1	33211-1190	490.00
4040080090	80	90	16	335	240	90	14.0	814.517	1	33211-0292	550.00
4040100110	100	110	16	375	250	90	18.5	814.518	1	33211-0293	632.00
4040100125	100	125	16	375	260	90	20.0	814.519	1	33211-0294	834.00
4040125140	125	140	16	450	280	95	24.0	814.521	1	33211-0295	873.00
4040150160	150	160	16	460	315	110	33.0	814.522	1	33211-0296	1'089.00
4040150180	150	180	16	460	340	120	40.0	814.523	1	33211-0297	1'224.00
4040200200	200	200	16	565	365	130	65.0	814.524	1	33211-1191	1'891.00

