

Hawle Flansch/PE-Steckmuffen-Schieber 4045

Anwendung: PE- und PVC-Rohre können direkt und schubsicher montiert werden.

Gehäuse: EN-GJS-400 (GGG 40), Dichtung EPDM, EWS-Beschichtung nach GSK, Schrauben INOX A2.

Betriebstemperatur max. 40 °C



Orig. Nr.	DN	Ø d mm	PN bar	H mm	L mm	t mm	Gewicht kg	NPK-Nr.	☞ Stück	Pestalozzi-Nr.	CHF Stück
4045050063	50	63	16	260	190	85	10,5	814.615	1	33211-1192	524,00
4045065075	65	75	16	330	205	85	15,5	814.626	1	33211-1193	563,00
4045080090	80	90	16	335	210	90	17,5	814.717	1	33211-1194	636,00
4045100110	100	110	16	375	225	90	22,0	814.738	1	33211-1195	727,00
4045100125	100	125	16	375	225	90	23,0	814.739	1	33211-1196	962,00
4045125140	125	140	16	450	240	95	33,5	814.761	1	33211-1197	1'006,00
4045150160	150	160	16	460	265	110	38,7	814.782	1	33211-1198	1'256,00
4045150180	150	180	16	460	275	120	43,0	814.783	1	33211-1199	1'418,00
4045200200	200	200	10	565	300	130	65,0	814.824	1	33211-1200	2'190,00
4045201200	200	200	16	565	300	130	65,0	814.824	1	33211-1201	2'190,00
4045200225	200	225	10	541	300	130	66,0		1	33211-2857	2'190,00
4045201225	200	225	16	541	300	130	66,0		1	33211-2858	2'190,00
4045250250	250	250	10	649	325	145	101,5		1	33211-2859	3'626,00
4045251250	250	250	16	649	325	145	101,5		1	33211-2861	3'626,00
4045250280	250	280	10	649	335	150	105,0		1	33211-2860	3'786,00
4045251280	250	280	16	649	335	150	105,0		1	33211-2862	3'786,00
4045300315	300	315	10	731	370	175	157,5		1	33211-2863	4'504,00
4045301315	300	315	16	731	370	175	157,5		1	33211-2864	4'504,00

2596

