



Vorschweissbund PE100 S-5 SDR 11 PN 16



Für Stumpf-, IR Plus- und Elektroschweissung, passend für Flanschverbindungen metrisch (ab d110 auch für ANSI/ASME B 16.5). Bis d280, passend zu Absperrklappe Typ 567/568 und 037/038/039, d20–d630: Profil-Flanschdichtung NBR Nr. 45 44 07, EPDM Nr. 48 44 07.
10 bar Gas / 16 bar Wasser.

Ab Grösse 75 mit Fase.

Lief.-Nr.	d mm	DN mm	d1 mm	d2 mm	L mm	L1 mm	L2 mm	NPK	Art.-Nr.
753 800 031	20	15	27	45	85	41	7		33305-0432
753 800 032	25	20	33	58	85	41	9	425.311	33305-0433
753 800 008	32	25	40	68	85	44	10	425.312	33305-0434
753 800 009	40	32	50	78	85	49	11	425.313	33305-0435
753 800 010	50	40	61	88	105	55	12	425.314	33305-0436
753 800 011	63	50	75	102	98	69	14	425.315	33305-0437
753 800 012	75	65	89	122	125	89	16	425.316	33305-0438
753 800 013	90	80	105	138	140	103	17	425.317	33305-0439
753 800 014	110	100	125	158	160	114	18	425.318	33305-0440
753 800 015	125	100	132	158	170	125	25	425.319	33305-0441
753 800 016	140	125	155	188	200	147	25	425.321	33305-0442
753 800 017	160	150	175	212	200	147	25	425.322	33305-0443
753 800 018	180	150	180	212	200	170	30	425.323	33305-0444
753 800 019	200	200	232	268	200	128	32	425.324	33305-0445
753 800 020	225	200	235	268	200	138	32	425.325	33305-0446
753 800 021	250	250	285	320	219	138	35	425.326	33305-0447
753 800 022	280	250	291	320	231	144	35	425.327	33305-1015
753 800 023	315	300	335	370	239	158	35	425.328	33305-1016

2548