



## Losflansch aus PP mit Stahleinlage



Material: PP-GF (30% glasfaserverstärkt) mit Stahleinlage, UV-resistent. Einsetzbar in Außeninstallationen. Anschluss Dimensionen: ISO 7005, EN 1092, DIN 2501.

Lief.-Nr.	d mm	DN mm	PN bar	D mm	D1 mm	D2 mm	H mm	NPK	Art.-Nr.
727 700 206	20	15	16	95	65	28	12		33305-0457
727 700 207	25	20	16	105	75	34	12	471.371	33305-0458
727 700 208	32	25	16	115	85	42	16	471.372	33305-0459
727 700 209	40	32	16	140	100	51	16	471.373	33305-0460
727 700 210	50	40	16	150	110	62	20	471.354	33305-0461
727 700 211	63	50	16	165	125	78	20	471.375	33305-0462
727 700 212	75	65	16	185	145	92	20	471.376	33305-0463
727 700 313	90	80	16	200	160	108	20	471.377	33305-0464
727 700 314	110	100	16	220	180	128	20	471.378	33305-0465
727 700 315	125	100	16	220	180	135	20	471.379	33305-0466
727 700 316	140	125	16	250	210	158	24	471.381	33305-0467
727 700 317	160	150	16	285	240	178	24	471.382	33305-0468
727 700 318	180	150	16	285	240	188	24	471.383	33305-0469
727 700 319	200	200	10	340	295	235	27	471.384	33305-0470
727 700 320	225	200	10	340	295	238	27	471.365	33305-0471
724 700 321	250	250	16	395	350	288	30	471.366	33305-0472
727 700 321	250	250	10	395	350	288	30	471.366	33305-0472 S
727 700 323	315	300	10	445	400	338	34	471.368	33305-0473

2541