

FRIAFIT-Muffe AM S-8 SDR 17 PN 10

- PE100 S-8 SDR 17 PN 10, Auch geeignet für Schweißung mit PE-Kanalrohren
- Maximal zulässiger Betriebsdruck 16 bar (Wasser) / 5 bar (Gas)



Orig. Nr.	d mm	D mm	L mm	Gewicht kg	NPK-Nr.	📦 Stück	📦 Stück		CHF Stück
680001	110	130	160	0.60	341.321	1	24	33306-0115	39.10
680013	125	146	160	0.62	341.322	1	22	33306-0116	47.00
680002	160	184	180	1.10	341.323	1	12	33306-0118	66.00
680003	180	207	180	1.34	341.323	1	8	33306-0105	92.00
680004	200	229	180	1.79	341.324	1		33306-0106	113.00
680005	225	254	200	2.83	341.324	1	4	33306-0107	140.00
680006	250	282	220	3.03	341.325	1		33306-0108	211.00
680007	280	316	220	3.80	341.325	1		33306-0104	277.00
680008	315	355	220	4.82	341.326	1		33306-0109	304.00
680009	355	400	220	6.10		1		33306-0110	373.00
680010	400	450	220	7.90		1		33306-0111	476.00
680011	450	506	270	8.40		1		33306-0250	600.00
680012	*500	562	270	14.90		1		33306-0251	800.00
680018	*560	630	380	24.80		1		33306-0252	1'250.00

*getrennte Schweißzonen

