



FRIALEN Druckanbohrventil DAV PE100 S-5 SDR 11 PN 16



Zulässiger Betriebsdruck: Wasser PN 16, Gas PN 5.

Lief.-Nr.	d1 mm	d2 mm	Ø da mm	L mm	NPK	Art.-Nr.
615955	50	32	20	164	963.314	33306-0221
615341	63	32	20	164	963.315	33306-0222
615342	63	40	20	164	963.335	33306-0223
615956	75	32	20	164	963.316	33306-0224
615344	90	32	30	200	963.317	33306-0225
615346	90	50	30	200	963.357	33306-0061
615347	90	63	30	200	963.377	33306-0226
615348	110	32	30	200	963.318	33306-0227
615350	110	50	30	200	963.358	33306-0062
615351	110	63	30	200	963.378	33306-0249
615352	125	32	30	200	963.319	33306-0228
615354	125	50	30	200	963.359	33306-0063
615355	125	63	30	200	963.379	33306-0229
615930	140	63	30	200		33306-0230
615356	160*	32	30	248	963.322	33306-0231
615358	160	50	30	248	963.322	33306-0064
615359	160	63	30	248	963.382	33306-0065
615361	180	32	30	248	963.323	33306-0232
615363	180	50	30	248	963.363	33306-0066
615364	180	63	30	248	963.383	33306-0233
615366	200	32	30	248	963.324	33306-0235
615368	200	50	30	248	963.364	33306-0067
615369	200	63	30	248	963.384	33306-0234
615374	225	32	30	248	963.325	33306-0236
615376	225	50	30	248	963.365	33306-0068
615377	225	63	30	248	963.385	33306-0237

2545

* Lieferung mit loser Reduziermuffe.