



FRIALEN Stützschelle SA PE 100 S-5 SDR 11 PN 16



Zulässiger Betriebsdruck: Wasser PN 16, Gas PN 5.

Lief.-Nr.	d1 mm	d2 mm	d3 mm	Ø da mm	L mm	NPK	Art.-Nr.
612757	63	32	22	20	100		33306-0190
612759	63	50	37	36	113	461.215	33306-0191
615020	75	50	38	36	82	461.216	33306-0192
615285	90	32	21	20	103		33306-0193
612819	90	63	50	46	103	461.237	33306-0071
615334	110	32	24	20	125		33306-0194
615031	110	50	39	36	132	461.218	33306-0195
612760	110	63	49	46	150	461.238	33306-0072
615411	110	90	70	65	115	461.278	33306-0196
615087	125	32	21	20	109		33306-0197
612761	125	63	47	46	109	461.239	33306-0073
615412	125	90	70	65	116	461.279	33306-0198
615584	125	110	86	84	116	461.319	33306-0199
612886	160	32	21	20	126		33306-0200
612762	160	63	47	46	140	461.242	33306-0074
615413	160	90	70	65	140	461.282	33306-0201
615739	160	110	86	84	140	461.322	33306-0202
615585	160	125	98	95	140	461.342	33306-0203
612763	180	63	47	46	109	461.243	33306-0075
615414	180	90	70	65	116	461.283	33306-0204
615948	180	110	86	84	136	461.323	33306-0205
615740	180	125	98	95	141	461.343	33306-0206
612764	200	63	47	46	109	461.244	33306-0076
612765	225	63	47	46	109	461.245	33306-0077
615415	225	90	70	65	130	461.285	33306-0207
616044	225	110	86	84	140	461.325	33306-0208
616045	225	125	97	95	146	461.345	33306-0209
616046	225	160	125	123	157	461.385	33306-0210

2545