



PE-Steckmuffen-T-Stück 7260, PN 16



Anwendung: PE- und PVC-Rohre können direkt und schubsicher montiert werden.
 Gehäuse:EN-GJS-400 (GGG 40), Dichtung EPDM, EWS-Beschichtung nach GSK, Schrauben INOX A2.

Betriebstemperatur max. 40 °C

Lief.-Nr.	Ø d1 mm	Ø d2 mm	L mm	h mm	t1 mm	t2 mm	NPK	Art.-Nr.
7260063063	63	63	235	120	85	85	441.215	33211-1242
7260075075	75	75	250	125	85	85	441.216	33211-1243
7260090090	90	90	270	135	85	85	441.217	33211-1244
7260110063	110	63	240	140	85	80	441.238	33211-1245
7260110090	110	90	270	145	85	85	441.258	33211-1246
7260110110	110	110	290	145	85	85	441.218	33211-1247
7260125090	125	90	275	150	85	85	441.259	33211-1248
7260125110	125	110	295	150	95	85	441.279	33211-1249
7260125125	125	125	305	155	90	90	441.219	33211-1250
7260140090	140	90	290	160	95	85	441.261	33211-1251
7260140110	140	110	305	160	95	85	441.281	33211-1252
7260140140	140	140	335	165	95	95	441.221	33211-1253
7260160090	160	90	310	170	105	85	441.262	33211-1254
7260160110	160	110	330	170	105	85	441.282	33211-1255
7260160160	160	160	380	190	105	105	441.222	33211-1257
7260180125	180	125	360	180	115	85	441.323	33211-1258
7260180180	180	180	415	210	115	115	441.223	33211-1259
7260200200	200	200	460	230	130	130	441.224	33211-1260

2596