



Combi-T mit PE-Steckmuffen 4350, PN 16



Anwendung: PE- und PVC-Röhre können direkt und schubsicher montiert werden.
 Gehäuse: EN-GJS-400 (GGG 40), Dichtung EPDM, EWS-Beschichtung nach GSK, Schrauben INOX A2.

Betriebstemperatur max. 40 °C

Lief.-Nr.	$\varnothing d1$ mm	$\varnothing d2$ mm	DN1 mm	DN2 mm	L mm	H mm	h mm	NPK	Art.-Nr.
4350090090	90	90	80	80	310	335	200	823.311	33211-1202
4350110063	110	63	100	50	290	260	220	823.332	33211-1203
4350110090	110	90	100	80	320	335	230	823.352	33211-1204
4350110110	110	110	100	100	340	375	230	823.312	33211-1205
4350125125	125	125	100	100	345	470	235	823.313	33211-1206
4350160090	160	90	150	80	350	335	250	823.354	33211-1207
4350160110	160	110	150	100	370	375	250	823.364	33211-1208
4350160125	160	125	150	100	370	470	255	823.374	33211-1209
4350160160	160	160	150	150	420	460	305	823.314	33211-1210
4350225090	225	90	200	80	410	335	280	823.355	33211-1211
4350225110	225	110	200	100	430	375	290	823.365	33211-1212

2596