



Geschweisste Siederohre, grau grundiert

Grau grundiert, Nach EN 10217-1 (DIN 1626/2458), aus Stahl P235TR1 (St37.0), innen und aussen sauber entfernte Schweissraupe, Kaltwasserprobe 50 bar, Rohrlänge ca. 6 Meter.

Ø-aussen mm	NW DN	Wandstärke mm	Gewicht kg	m	m		CHF m
42.4	32	2.3	2.27	6	366	30103-0060	17.80
48.3	40	2.3	2.61	6	366	30103-0062	20.40
60.3	50	2.9	4.11	6	222	30103-0065	31.15
76.1	65	2.9	5.24	6	222	30103-0068	39.65
88.9	80	3.2	6.76	6	114	30103-0070	51.15
108.0	-	3.6	9.27	6	114	30103-0072	70.00
114.3	100	3.6	9.83	6	114	30103-0073	73.35
133.0	-	4.0	12.70	6	84	30103-0076	95.40
139.7	125	4.0	13.40	6	60	30103-0077	99.75
159.0	-	4.5	17.10	6	78	30103-0079	127.45
168.3	150	4.5	18.20	6	60	30103-0080	135.45
219.1	200	4.5	23.80	6	42	30103-0081	175.15

