



Geschweisste Siederohre, schwarz

Nach EN 10217-1 (DIN 1626/2458), aus Stahl S195T (St 37.0), innen und aussen sauber entfernte Schweissraupe, Kaltwasserprobe 50 bar, Rohrlänge ca. 6 Meter, schwarz

Ø-aussen mm	NW DN	Wandstärke mm	Gewicht kg	☞ m		CHF m
33.7	25	2.3	1.78	6	30103-0002	13.20
38	-	2.3	2.04	6	30103-0003	15.15
42.4	32	2.3	2.27	6	30103-0004	16.80
44.5	-	2.3	2.41	6	30103-0005	14.70
48.3	40	2.3	2.61	6	30103-0006	19.35
60.3	50	2.9	4.11	6	30103-0009	30.25
76.1	65	2.9	5.24	6	30103-0012	38.60
88.9	80	3.2	6.76	6	30103-0014	49.85
101.6	-	3.6	8.76		30103-0015	55.95
108	-	3.6	9.27	6	30103-0016	68.10
114.3	100	3.6	9.83	6	30103-0017	72.35
139.7	125	4.0	13.40	6	30103-0021	98.35
159	-	4.5	17.10	6	30103-0023	110.25
168.3	150	4.5	18.20	6	30103-0024	133.50
219.1	200	4.5	23.70	6	30103-0026	175.00
273	250	5	33.12	6	30103-0027	255.50
323.9	300	5.6	43.97	6	30103-0028	343.55
355.6	350	5.6	48.20	6	30103-0029	p)
406.4	400	6.3	62.40	6	30103-0030	p)
457.2	450	6.3	70.00	6	30103-0101	p)
508.0	500	6.3	78.00	6	30103-0102	p)

p) Preis auf Anfrage

