



Geschweisste Gasrohre, verzinkt

Stahl verzinkt, nach EN 10255-M (DIN 2440), mittelschwere Reihe aus S 195 T (St. 33.0), verzinkt nach EN 10240 A1 (DIN 2444) druckgeprüft, Herstellungslänge ca. 6.0 m.

| Dim. Zoll | NW DN | Ø-aussen mm | Wandstärke mm | Gewicht kg | ☎ m | ☎ m | | CHF m |
|--------------|----------|----------------|------------------|---------------|--------|--------|------------|----------|
| 3/8 | 10 | 17.2 | 2.35 | 0.85 | 6 | 1242 | 30101-0033 | 12.40 |
| 1/2 | 15 | 21.3 | 2.65 | 1.22 | 6 | 1260 | 30101-0034 | 14.60 |
| 3/4 | 20 | 26.9 | 2.65 | 1.58 | 6 | 1500 | 30101-0035 | 18.10 |
| 1 | 25 | 33.7 | 3.25 | 2.44 | 6 | 3000 | 30101-0036 | 25.10 |
| 5/4 | 32 | 42.4 | 3.25 | 3.14 | 6 | 1440 | 30101-0037 | 32.10 |
| 1 1/2 | 40 | 48.3 | 3.25 | 3.61 | 6 | 1680 | 30101-0038 | 36.90 |
| 2 | 50 | 60.3 | 3.65 | 5.10 | 6 | 900 | 30101-0039 | 52.10 |
| 2 1/2 | 65 | 76.1 | 3.65 | 6.51 | 6 | 240 | 30101-0040 | 66.50 |
| 3 | 80 | 88.9 | 4.05 | 8.47 | 2 | 180 | 30101-0041 | 86.40 |
| 4 | 100 | 114.3 | 4.5 | 12.10 | 4 | 162 | 30101-0042 | 122.95 |

