



### Siederrohrbogen, nahtlos, 5d 90°

Aus Stahl P235GH TC1, nach (DIN2605/1) neu EN 10253-2 Typ A.

da mm	s mm	Gewicht kg	Ø-aussen mm	Wandstärke mm	Radius mm	☞ Stück	☞☞ Stück		CHF Stück
21.3	2.0	0.08	21.3	2.0	42.5	1	100	30203-0080	16.20
26.9	2.3	0.14	26.9	2.3	57.5	1	100	30203-0081	16.20
33.7	2.6	0.23	33.7	2.6	72.5	1	100	30203-0082	17.80
42.4	2.6	0.38	42.4	2.6	92.5	1		30203-0084	20.75
48.3	2.6	0.54	48.3	2.6	107.5	1		30203-0085	28.25
57.0	2.9	0.84	57.0	2.9	128.0	1		30203-0086	42.20
60.3	2.9	0.94	60.3	2.9	135.0	1	25	30203-0087	35.30
76.1	2.9	1.56	76.1	2.9	175.0	1	20	30203-0088	49.30
88.9	3.2	2.33	88.9	3.2	205.0	1		30203-0089	70.70
101.6	3.6	3.52	101.6	3.6	237.5	1		30203-0090	135.60
108.0	3.6	3.84	108.0	3.6	252.5	1		30203-0091	135.60
114.3	3.6	4.73	114.3	3.6	270.0	1		30203-0092	129.95
133.0	4.0	7.35	133.0	4.0	312.5	1	50	30203-0093	218.10
139.7	4.0	8.11	139.7	4.0	330.0	1	50	30203-0094	198.85
159.0	4.5	10.82	159.0	4.5	375.0	1		30203-0095	311.00
168.3	4.5	11.26	168.3	4.5	390.0	1		30203-0096	299.65
219.1	6.3	26.50	219.1	6.3	510.0	1		30203-0097	649.00

