



Sattelstutzen

Modell kurz, nahtlos, aus Stahl P235GH TC1 (2345.8-1), zum Einschweissen in Rohre mit gleichem Durchmesser, Ausführung nach (DIN2618) neu EN 10253-2.

Ø-aussen mm	Wandstärke mm	Höhe mm	Gewicht kg	Stück		CHF Stück
26.9	2.3	50	0.09	1	30204-0149	25.80
33.7	2.6	60	0.08	1	30204-0150	27.30
42.4	2.6	60	0.13	1	30204-0151	29.05
48.3	2.6	70	0.19	1	30204-0152	27.65
60.3	2.9	90	0.28	1	30204-0153	27.60
76.1	2.9	110	0.38	1	30204-0154	39.95
88.9	3.2	125	0.62	1	30204-0155	54.55
108.0	3.6	150	0.94	1	30204-0156	132.20
114.3	3.6	150	1.01	1	30204-0157	80.30
133.0	4	160	1.70	1	30204-0158	112.55
139.7	4	160	1.95	1	30204-0159	129.25
159.0	4.5	170	2.76	1	30204-0160	228.40
168.3	4.5	170	2.94	1	30204-0161	212.60
219.1	6.3	220	6.62	1	30204-0162	449.20
273.0	6.3	230	12.52	1	30204-0163	668.95
323.9	7.1	250	21.54	1	30204-0164	1'109.85
355.6	8	270	22.20	1	30204-0165	1'645.55
406.8	8.8	280	30.00	1	30204-0166	2'309.75

