



Optipress-Therm-Reduktion, mit Einsteckende 55021

• PN 16, Stahl 1.0308 verzinkt



Orig. Nr.	D mm	d mm	z mm	L mm	Gewicht kg	NPK-Nr.	 Stück	 Stück		CHF Stück
5502124	18	15	30	52	0.01	255.313	5	500	32108-1596	2.20
5502126	22	15	35	57	0.04	322.313	5	400	32108-1597	2.20
5502127	22	18	38	60	0.05	322.314	5	400	32108-1598	2.35
5502129	28	15	50	72	0.06	255.315	5	250	32108-1599	3.05
5502130	28	18	46	68	0.05	255.315	5	300	32108-1600	3.05
5502131	28	22	41	64	0.06	322.315	5	240	32108-1601	3.00
5502132	35	15	58	80	0.07	255.316	5	200	32108-1815	4.10
5502133	35	22	49	73	0.07	255.316	5	150	32108-1602	3.45
5502134	35	28	43	67	0.08	322.316	5	180	32108-1603	3.45
5502136	42	22	68	91	0.13	255.317	5	100	32108-1817	8.45
5502137	42	28	66	90	0.12	255.317	5	120	32108-2098	8.45
5502138	42	35	54	80	0.12	322.317	1	90	32108-1604	7.70
5502135	54	18	90	112	0.18	255.318	1	40	32108-2262	24.65
5502139	54	22	86	109	0.18	255.318	1	40	32108-1605	22.40
5502142	54	35	72	98	0.19	255.316	1	40	32108-1819	22.40
5502140	54	28	79	103	0.18	255.318	1	40	32108-1606	22.40
5502141	54	42	66	102	0.21	322.318	1	45	32108-1607	22.40
5502171	64	54	71	111	0.40	255.324	1	30	32108-1751	38.40
5502169	76.1	35	88	114	0.35	255.321	1	35	32108-2263	56.70
5502170	76.1	42	86	123	0.35	255.321	1	30	32108-2264	56.70
5502172	76.1	54	83	123	0.35	255.321	1	16	32108-1752	37.25
5502173	76.1	64	83	126	0.35	322.319	1	20	32108-1753	48.40
5502174	88.9	54	90	130	0.40	255.322	1	24	32108-1754	44.95
5502175	88.9	64	89	132	0.40	255.322	1	24	32108-1755	48.40
5502176	88.9	76.1	82	132	0.40	322.321	1	20	32108-1756	47.35
5502177	108.0	54	109	149	0.45	255.323	1	12	32108-1757	52.80
5502179	108.0	76.1	101	151	0.45	255.323	1	12	32108-1759	52.80
5502180	108.0	88.9	95	145	0.45	322.322	1	12	32108-1760	52.80

