

Optipress-Therm-Übergang, mit Innengewinde 55033

- PN 16, Stahl 1.0308 verzinkt



Orig.-Nr.	d mm	Rp Zoll	z mm	L mm	S mm	Gewicht kg	NPK-Nr.	☒ Stück	☒ Stück		CHF Stück
5503321	15	3/8	5	37	22	0.04	325.312	5	400	32108-1918	6.25
5503322	15	1/2	6	41	24	0.04	255.632	5	400	32108-1622	6.25
5503327	15	3/4	8	45	30	0.07	255.632	5	300	32108-1919	7.60
5503323	18	1/2	6	41	27	0.06	255.633	5	360	32108-1623	7.10
5503324	18	3/4	7	44	34	0.06	325.313	5	250	32108-1624	7.40
5503328	22	1/2	4	41	32	0.06	255.634	5	300	32108-1920	10.20
5503325	22	3/4	6	45	34	0.07	255.634	5	300	32108-1625	7.40
5503329	22	1	7	48	36	0.07	325.314	5	200	32108-1921	9.20
5503330	28	1/2	-	38	38	0.12	255.635	5	250	32108-2265	12.70
5503331	28	3/4	3	44	38	0.13	255.635	5	160	32108-1922	11.55
5503326	28	1	7	48	38	0.11	325.315	5	200	32108-1626	9.80
5503332	35	3/4	2	43	46	0.10	255.636	5	100	32108-1923	15.60
5503336	35	1	-	43	46	0.15	255.636	5	150	32108-2266	15.60
5503333	35	1 1/4	7	52	50	0.17	325.316	5	150	32108-1924	15.60
5503337	42	1 1/4	16	71	46	0.30	255.637	1	60	32108-2267	18.55
5503334	42	1 1/2	8	63	55	0.23	325.317	1	40	32108-1925	18.55
5503335	54	2	8	72	70	0.41	325.318	1	45	32108-1926	26.75
5503370	64	2	21	88	65	0.40	255.644	1	40	32108-2106	99.30
5503371	64	2 1/2	28	98	82	0.40	255.644	1	36	32108-2107	109.25
5503372	76.1	2 1/2	28	104	82	0.60	255.641	1	16	32108-2108	118.10

