

Safe Sattelstück gepresst 90° PSU

• Gepresst, mit strömungsgünstigem Radius, Stahl sendzimirverzinkt



Orig. Nr.	Ø d mm	Ø d3 mm	l3 mm	Gewicht kg	Stück	Stück		CHF Stück
252102	100	80	60	0.10	1	60	31401-0244	12.55
252115	125	80	75	0.09	1	60	31401-0252	13.90
252142	160	80	92	0.10	1	70	31401-0253	11.60
252165	200	80	112	0.09	1	70	31401-0254	13.05
252104	100	100	65	0.14	1	75	31401-0245	12.55
252117	125	100	78	0.18	1	80	31401-0255	13.90
252144	160	100	95	0.14	1	90	31401-0256	11.60
252167	200	100	115	0.19	1	90	31401-0257	13.40
252194	250	100	140	0.18	1	90	31401-0258	11.60
252119	125	125	83	0.19	1	40	31401-0246	13.90
252146	160	125	100	0.25	1	50	31401-0259	13.25
252169	200	125	115	0.18	1	52	31401-0260	13.70
252196	250	125	145	0.25	1	50	31401-0261	13.70
252244	315	125	178	0.23	1	54	31401-0262	13.70
277320	160	150	100	0.34	1	25	31401-0263	16.25
252170	200	150	120	0.30	1	30	31401-0247	16.75
252197	250	150	145	0.32	1	35	31401-0264	16.75
252149	160	160	105	0.26	1	20	31401-0248	17.85
252172	200	160	125	0.27	1	25	31401-0265	17.40
252199	250	160	150	0.26	1	25	31401-0266	16.75
252247	315	160	182	0.24	1	25	31401-0267	16.75
252152	180	180	115	0.48	1	42	31401-0249	23.35
252173	200	180	125	0.45	1	40	31401-0268	21.95
252200	250	180	150	0.41	1	34	31401-0269	21.95
252248	315	180	182	0.40	1	35	31401-0270	20.25
252174	200	200	125	0.39	1	32	31401-0250	20.25
252201	250	200	150	0.47	1	32	31401-0271	22.80
252249	315	200	182	0.46	1	32	31401-0272	22.80
252203	250	250	150	0.47	1	15	31401-0251	37.85
252251	315	250	182	0.71	1	16	31401-0273	37.55

Andere Dimensionen auf Anfrage

