





Siederrohrbogen, nahtlos, 3d 45°

nach EN 10253-2 Typ A (DIN 2605/1), aus Stahl S235 (St. 37.0), mit eingeschränktem Ausnutzungsgrad.

Ø-aussen mm	Wandstärke mm	Radius mm	Gewicht kg	 Stück	 Stück	CHF Stück
21.3	2.0	28	0.02	1		9.80
26.9	2.3	29	0.03	1		9.80
33.7	2.6	38	0.06	1		9.25
42.4	2.6	48	0.09	1		11.00
48.3	2.6	57	0.13	1	100	13.75
57.3	2.9	75	0.22	1		21.90
60.3	2.9	76	0.26	1		20.65
76.1	2.9	95	0.45	1		29.75
88.9	3.2	114	0.62	1		42.35
114.3	3.6	152	1.16	1		74.00
101.6	3.0	134	0.92	1		70.60
108.0	3.6	143	0.96	1		94.15
139.7	4.0	190	2.08	1		127.45
168.3	4.5	229	3.19	1		186.10
219.1	6.3	305	7.87	1		290.65
273.0	6.3	381	22.45	1		522.00
323.9	7.1	457	20.00	1		834.25
355.6	8.0	533	28.60	1		1'198.55
406.4	8.8	610	41.10	1		1'579.65

