

Optiflex-Flowpress-Rohr formstabil 87157

- PN 10, in Stangen, PE-Xc-Rohr aluminiumverstärkt, mit Diffusionssperre, Kunststoff



| Orig. Nr. | d mm | S mm | L m | Gewicht kg | NPK-Nr. | ☞ m | ☞☞ m | | CHF m |
|-----------|---------|---------|--------|---------------|---------|--------|---------|------------|----------|
| 8715721 | 16 | 2.2 | 5 | 0.11 | 251.221 | 5 | 4500 | 32107-0941 | 5.10 |
| 8715722 | 20 | 2.8 | 5 | 0.15 | 251.222 | 5 | 3100 | 32107-0942 | 6.60 |
| 8715723 | 25 | 2.7 | 5 | 0.19 | 251.223 | 5 | 2000 | 32107-0943 | 10.55 |
| 8715724 | 32 | 3.2 | 5 | 0.31 | 251.224 | 5 | 1300 | 32107-0944 | 16.75 |
| 8715725 | 40 | 3.5 | 5 | 0.39 | 251.225 | 5 | 400 | 32107-0945 | 26.25 |

Formstabile Optiflex-Flowpress-Rohre dürfen nur mit Optiflex-Flowpress Pressfittings verarbeitet werden

