



Nahtlose Siederohre, schwarz

Nach ISO-Empfehlung R64, aus Stahl St. 37.0, Kaltwasserprobedruck 40 bar, Rohrlänge von 5 bis 7m.

Ø-aussen mm	NW DN	Wandstärke mm	Gewicht kg	☞ m		CHF m
31.8	-	2.6	1.88	6	30104-0001	34.30
33.7	25	2.6	2.01	6	30104-0002	25.30
38	-	2.6	2.29	6	30104-0003	37.80
42.4	32	2.6	2.57	6	30104-0004	31.85
44.5	-	2.6	2.70	6	30104-0005	44.45
48.3	40	2.6	2.95	6	30104-0006	36.60
51	-	2.6	3.12	6	30104-0007	50.25
54	-	2.6	3.30	6	30104-0008	53.15
57	-	2.9	3.90	6	30104-0009	62.85
60.3	50	2.9	4.14	6	30104-0010	49.95
63.5	-	2.9	4.36	6	30104-0011	70.15
70	-	2.9	4.83	6	30104-0012	77.70
76.1	65	2.9	5.28	6	30104-0013	63.70
82.5	-	3.2	6.31	6	30104-0014	77.05
88.9	80	3.2	6.81	6	30104-0015	81.55
101.6	-	3.6	8.76	6	30104-0016	139.80
108	-	3.6	9.33	6	30104-0017	148.90
114.3	100	3.6	9.90	6	30104-0018	118.45
127	-	4	12.20	6	30104-0019	196.65
133	-	4	12.80	6	30104-0020	206.30
139.7	125	4	13.50	6	30104-0021	163.45
152.4	-	4.5	16.40	6	30104-0022	266.45
159	-	4.5	17.10	6	30104-0023	277.85
168.3	150	4.5	18.10	6	30104-0024	221.85
177.8	-	5	21.30	6	30104-0025	346.10
193.7	-	5.6	26.00	6	30104-0026	420.95
219.1	200	6.3	33.10	6	30104-0027	404.65
244.5	-	6.3	37.10	6	30104-0028	603.85
267	-	6.3	40.60	6	30104-0029	664.70
273	250	6.3	41.60	6	30104-0030	505.70
298.5	-	7.1	51.10	6	30104-0031	893.00
323.9	300	7.1	55.60	6	30104-0032	728.15
355.6	350	8	68.30	6	30104-0033	1'192.40
368	-	8	70.80	6	30104-0034	1'238.10
406.4	400	8.8	85.90	6	30104-0035	1'332.00
419	-	10	101.00	6	30104-0036	1'879.95

